

Suzuki DF6

Overview

The DF4, DF5 and DF6 make the advantages of advanced clean burning, fuel saving four stroke technologies available to the portable engine user.

Ease of operation and handling ranked very highly in the design criteria and power is provided by a single cylinder OHV engine with a displacement of 138cc. Combined with the light weight this produces excellent low to mid-range torque and fast acceleration. A digital capacitor discharge ignition system combines the ignition coil and control processor into a corrosion resistant single unit which produces precise control of the ignition timing, gives stable idling and has a built-in rev limiter. The tiller handle is mounted on the steering bracket allowing the operator to sit well forward improving weight distribution. Other features include 180 degrees steering providing good manoeuvrability even in shallow water drive, a 1.5 litre integral fuel tank and a large carrying handle.

Specifications

Recommended transom height	381mm (15in)
Weight	25.0Kg
Bore x Stroke	62x46mm
Propeller Selection (pitch)	6
Starting System	Manual
Engine Type	OHV
Fuel Delivery System	Carburetor
No. of Cylinders	1
Piston Displacement cm ³	138cc
Maximum Output	4.4kW
Full Throttle Operating Range	4,750 – 5,750
Steering	Tiller
Oil Pan Capacity	0.7Ltr
Fuel Tank Capacity	1.5Ltrs
Ignition System	Digital CDI

Alternator	12V 6A(OP.)
Engine Mounting	Bushing Type
Trim Method	Manual Trim and Tilt
Gear Ratio	1.92:1
Gear Shift	F-N-R
Exhaust	Above Prop Exhaust

